SPEAKER

PRODUCT SHEET & SPECIFICATIONS

G-1052 MAGNACAST II INDOOR/OUTDOOR MASS NOTIFICATION SPEAKER



FUNCTION

The Magnacast II Indoor/Outdoor Mass Notification speaker allows for fewer units to be installed in large indoor and outdoor areas, lowering installation and long-term maintenance costs. Best-in-industry voice quality and intelligibility combined with sharp and high impact tone capability make it the right choice for ensuring critical messages are heard and understood.

-APPLICATION

- + Emergency Notification
- + Campus Communications
- + Manufacturing Facilities
- + Fire & Life Safety
- + Warehouses
- + Corporate Campuses
- + Airports/Airport Hangars
- + Arenas/Stadiums
- + Parking Structures



SPEAKER

Model

G-1052

MAGNACAST II SPEAKER

- ACOUSTIC SPECIFICATIONS

- + Frequency Response: 400Hz 7000Hz
- + Directionality: ±30 degrees

-POWER REQUIREMENT

+ Input Voltage:

25, 70, 100 VRMS

+ Power 45 watts

+ Power Selections:

25V	70V	100V
3W	24W	45W
2W	16W	32W
1.5W	12W	24W
ıW	8W	16W
0.5W	4W	8W

+ SPL Power Selections:

Power Selection	SPL
45W	139dB
32W	137dB
24W	136dB
16W	134dB
12W	133dB
8W	131dB
4W	129dB
3W	128dB
2W	126dB
1.5W	124dB
ıW	122dB
0.5W	119dB

- PHYSICAL SPECIFICATIONS

- + Dimensions 10.0" H X 10.0" W X 10.7" L
- + Weight 9lbs
- + Housing Material Composite

